

Libraries

| Name | Process | Form Factor |
|--------------------------------|---------|---------------|
| RGO_TSMC16_18V33_FFC_20C_SD | FFC | Staggered CUP |
| RGO_TSMC12_18V33_FFC_LL_20C_SD | FFC_LL | Staggered CUP |

Summary

The SD library provides bidirectional SD 3.0 signaling cells. It is compatible with revision 3.01 of the SD Specifications, Part 1, Physical Layer Specification. It is also compatible with the Embedded Multi-Media Card (eMMC) Electrical Standard (5.1) (JESD84-B51 – February 2015). This library is offered as a supplement to the standard GPIO libraries provided by Aragio Solutions.

These libraries are offered at both 16nm and a 12nm shrink. They are available in a staggered CUP wire bond implementation with a flip chip option.

To utilize these cells in the pad ring, an additional library is required – 3.3V Support: Power. That library contains the necessary power cells, the POC and VREF cells, and a rail splitter to isolate the SD cells in their own power domain as recommended. It also contains an input-only buffer, isolated analog I/O, and a full complement of power cells along with corner and spacer cells to assemble a complete pad ring by abutment. The rail splitter allows multiple power domains to be isolated in the same pad ring while maintaining continuous VDD/VSS for robust ESD protection.

ESD Protection:


- JEDEC compliant
 - 2KV ESD Human Body Model (HBM)
 - 500 V ESD Charge Device Model (CDM)

Latch-up Immunity:


- JEDEC compliant
 - Tested to I-Test criteria of $\pm 100\text{mA}$ @ 125°C

Cell Size & Form Factor

Staggered (pad-limited) – $32.208\mu\text{m} \times 220.032\mu\text{m}$



STP_BI_016_1833V_SD3



Bidirectional SD 3.0 Driver Features

- Dual voltage operation (1.8V & 3.3V)
- Programmable drive strength
- Selectable output slew-rate (slow / fast)
- Selectable schmitt trigger input
- Programmable input options (pull-up, pull-down, or plain input)
- Fully compatible with Aragio Solutions 3.3V I/O library offerings
- Power-up sequencing independent design with Power-on Control

Vertical-only (_V) and horizontal-only (_H) variants provided.

Recommended operating conditions

| Description | Min | Nom | Max | Units |
|--|--------------------|-----|-------------------|------------------|
| V_{VDD} Core supply voltage | 0.72 | 0.8 | 0.88 | V |
| T_J Junction temperature | -40 | 25 | +125 | $^\circ\text{C}$ |
| V_{PAD} Voltage at IO | -0.3 | | $V_{DVDD} + 0.3$ | V |
| V_{DVDD} I/O supply voltage | 2.7 | 3.3 | 3.63 | V |
| V_{IH} Input logic high | $0.625 * V_{DVDD}$ | - | $V_{DVDD} + 0.3$ | V |
| V_{IL} Input logic low | $V_{DVSS} - 0.3$ | - | $0.25 * V_{DVDD}$ | V |
| $V_{HYS}^{[1]}$ Input hysteresis voltage | 0.2 | - | - | V |
| V_{DVDD} I/O supply voltage | 1.7 | 1.8 | 1.95 | V |
| V_{IH} Input logic high | $0.65 * V_{DVDD}$ | - | $V_{DVDD} + 0.3$ | V |
| V_{IL} Input logic low | $V_{DVSS} - 0.3$ | - | $0.35 * V_{DVDD}$ | V |
| $V_{HYS}^{[1]}$ Input hysteresis voltage | $0.1 * V_{DVDD}$ | - | - | V |

[1] When SMT = 1.

Characterization Corners (16nm)

| Model | LPE Type | VDD=0.8V | DVDD [1] | Temp |
|-------|------------------|----------|----------|-------|
| FFGNP | Cbest_CCbest_T | +10% | +10% | -40°C |
| FFGNP | Cbest_CCbest_T | +10% | +10% | 0°C |
| FFGNP | Cbest_CCbest_T | +10% | +10% | 125°C |
| FFG | Ctypical | +10% | +10% | 125°C |
| TT | Ctypical | nominal | nominal | 25°C |
| TT | Ctypical | nominal | nominal | 85°C |
| SSGNP | Cworst_CCworst_T | -10% | -10% | -40°C |
| SSGNP | Cworst_CCworst_T | -10% | -10% | 0°C |
| SSGNP | Cworst_CCworst_T | -10% | -10% | 125°C |

[1] DVDD = 1.8V, 3.0 & 3.3V

Characterization Corners (12nm)

| Model | LPE Type | VDD=0.8V | DVDD [1] | Temp |
|-------|----------------|----------|----------|-------|
| FF | Cbest_CCbest | +10% | +10% | -40°C |
| FF | Cbest_CCbest | +10% | +10% | 0°C |
| FF | Cbest_CCbest | +10% | +10% | 125°C |
| FFG | Ctypical | +10% | +10% | 125°C |
| TT | Ctypical | nominal | nominal | 25°C |
| TT | Ctypical | nominal | nominal | 85°C |
| SS | Cworst_CCworst | -10% | -10% | -40°C |
| SS | Cworst_CCworst | -10% | -10% | 0°C |
| SS | Cworst_CCworst | -10% | -10% | 125°C |

[1] DVDD = 1.8V, 3.0 & 3.3V

© 2011-2018 Aragio Solutions. All rights reserved.

Information in this document is subject to change without notice. Aragio Solutions may have patents, patent applications, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Aragio, the furnishing of this document does not give you any license to the patents, trademarks, copyrights, or other intellectual property.

Published by:

Aragio Solutions
2201 K Avenue
Section B Suite 200
Plano, TX 75074-5918
Phone: (972) 516-0999
Fax: (972) 516-0998
Web: <http://www.aragio.com/>

While every precaution has been taken in the preparation of this book, the publisher assumes no responsibility for errors or omissions, or for damages resulting from the use of the information contained herein. This document may be reproduced and distributed in whole, in any medium, physical or electronic, under the terms of a license or nondisclosure agreement with Aragio.

Printed in the United States of America